

# MU CONNECTOR

光纖連接器零件

PART NO. :



## Specification

	SM	MM
Insertion Loss	0.1dB typical	0.15dB
Return Loss	≥55dB typical (PC)	
Durability	< 0.1dB typical Change , 500 matings	< 0.2dB
Operating Temperature	-40°C to +75°C	
Ferrule Hole Sizes	125.5μm +1/-0, Concentricity: ≤ 1μm	127μm (MM)

## Order

MU- **A** **B** **C** **D** **E** - 300

**A** Connector      **B** Ferrule      **C** Housing      **D** Boot Type      **E** Boot Color

- |                          |                                |   |   |  |
|--------------------------|--------------------------------|---|---|--|
| <b>1</b> : Pre-Assembled | <b>1</b> : SM<br><b>2</b> : MM | <b>1</b> : Blue<br><b>2</b> : Black<br><b>3</b> : Beige<br><b>4</b> : Red<br><b>5</b> : Brown<br><b>6</b> : Yellow<br><b>7</b> : MU - J | <b>1</b> : 2.0 mm cable standard<br><b>2</b> : 1.6 mm cable<br><b>3</b> : 1.0 mm fiber<br><b>2</b> : 1.0 mm fiber short | <b>1</b> : Blue<br><b>2</b> : Black<br><b>3</b> : Red<br><b>4</b> : Yellow<br><b>5</b> : Beige<br><b>6</b> : Green<br><b>7</b> : Gray<br><b>8</b> : White<br><b>9</b> : Lavender |
|--------------------------|--------------------------------|---|---|--|

MU- **A** **B** - 350

**A** Duplex Clip      **B** Duplex Clip Color

- |                                |                  |
|--------------------------------|------------------|
| <b>1</b> : Type 1 (Horizontal) | <b>1</b> : Brown |
| <b>2</b> : Type 2 (Vertical)   | <b>2</b> : Black |



Type 2



Type 1

# MU CONNECTOR

光纖連接器零件

PART NO. :

